SANTO 70288 DT

Fridge freezer

Operating Instructions

Dear customer,

Before placing your new refrigerator/freezer into operation please read these operating instructions carefully. They contain important information for safe use, for installation and for care of the appliance.

Please keep these operating instructions for future reference. Pass them on to possible new owners of the appliance.



Notes which are important for your safety or for the proper functioning of the appliance are stressed with a warning triangle and/or with signal words (Warning!, Caution!, Attention!). Please observe the following carefully.

Additional information regarding operation and practical applications of the appliance appear after this symbol.

Tips and notes concerning economical and environmentally sound use of the appliance are marked with the flower.

In the event of a malfunction, these operating instructions contain information on how to rectify faults yourself, see the "Something Not Working" section.

For futher assistance contact your local AEG service Force Centre, see the chapter "Service and Spare Parts.

Contents

Safety
Disposal
Remove transport safeguard
Fitting the door handles7
Prior to Initial Start-Up8
Starting up and temperature regulation
Interior Accessories
Fresh food refrigeration
Freezing and storing frozen food9
Preparation of Ice Cubes10
Freezing Calender10
Defrosting
Switching off the appliance11
Cleaning and Care12
Energy Saving Tips
What to do if.13Correcting Malfunctions.13Changing the light bulb.15
Service and Spare Parts16
Customer Care Department16
Guarantee Conditions17
Installation - Electrical Connection.18Positioning - Rear spacer.19Reversing the door.20
Regulations, Standards, Guidelines

▲ Safety

The safety aspects of our appliance comply with accepted technical standards and the German Appliance Safety Law. Nevertheless, we consider it our obligation to make you aware of the following safety information: Intended use

- The appliance is intended for use in the home. It is suitable for the cooling, freezing and storing of frozen food, as well as for making ice. If the appliance is used for purposes other than those intended or used incorrectly, no liability can be accepted by the manufacturer for any damage that may be caused.
- Alterations or changes to the appliance are not permitted for reasons of safety.
- If you use the appliance in a commercial application or forpurposes other than the cooling, freezing or frozen storage of foods, please observe all valid legal regulations for your application.

Prior to initial start-up

• Check the appliance for transport damage. Under no circumstance should a damaged appliance be plugged in! In the event of damage, please contact the vendor.

Refrigerant

The refrigerant isobutane (R600a) is contained within the refrigerant circuit of the appliance, a natural gas with a high level of environmental compatibility, which is nevertheless flammable.

- During transportation and installation of the appliance, be certain that none of the components of the refrigerant circuit become damaged.
- If the refrigerant circuit should become damaged:
- avoid open flames and sources of ignition;
- thoroughly ventilate the room in which the appliance is situated.

Safety of children

- Packaging (e.g. wraps, polystyrene) can be dangerous for children. There is a risk of suffocation! Keep packaging material away from children!
- Please make old appliances unusable prior to disposal. Pull out the mains plug, cut off the mains cable, break or remove spring or boltcatches, if fit-ted. By doing this you ensure that children cannot lock themselves in the appliance when playing (there is risk of suffocation!)or get themselves into other dangerous situations.
- Often children cannot recognise the hazards present in household appliances. It is therefore important that you ensure adequate supervision and never let children play with the appliance!

Daily Operation

- Containers with flammable gases or liquids can leak at low temperatures. There is a risk of an explosion! Do not store any containers with flammable materials such as, for example, spray cans, fire extinguisher refill cartridges etc in the refrigerator/freezer.
- Bottles and cans must not be placed in the freezer compartment. They can burst when the contents freeze, high carbonate content drinks can even explode! Never store lemonade, juices, beer, wine, sparkling wine etc. in the freezer compartment. Exception: high alcohol content spirits can be stored in the freezer compartment.
- Do not put ice creams or ice cubes in the mouth immediately after removal from the freezer compartment. Very cold ice can freeze to the lips or tongue and cause injury.
- Do not touch frozen food with wet hands. Your hands could freeze to the food.
- Do not operate any electrical appliances in the refrigerator/freezer (e.g. electric ice cream makers, mixers etc.).
- Before cleaning the appliance, always switch off the appliance and unplug it, or pull the house fuse or switch off the circuit breaker.
- When unplugging always pull the plug from the mains socket, do not pull on the cable.

Service

• Under no circumstances should you attempt to repair the appliance yourself. Repairs carried out by inexperienced persons may cause injury or serious malfunctioning. Contact your local AEG Service Force Centre.

Disposal Appliance Packaging Information

All materials are environmentally sound! They can be dumped or burned at an incinerating plant without danger!

About the materials: The plastics can be recycled and are identified as follows:

>PE< for polyethylene, e.g. the outer covering and the bags in the interior. >PS< for polystyrene foam, e.g. the pads, which are all free of chlorofluorocarbon.

The carton parts are made from recycled paper and should be disposed of at a waste-paper recycling collection location.

Disposal of old Appliances

For environmental reasons, refrigeration appliances must be disposed of properly. This applies to your old appliance, and – at the end of its service life – for your new appliance as well.



Warning! Before disposing of old appliances make them inoperable. Remove plug from mains, sever the power cable, remove or destroy any snap or latch closures, to prevent small children being trapped inside.

- Use an authorised disposal site.
- The symbol A on the product or on its packaging indicates that this product may not be treated as household waste. Instead it shall be handed over to the applicable collection point for the recycling of electrical and electronic equipment. By ensuring this product is disposed of correctly, you will help prevent potential negative consequences for the environment and human health, which could otherwise be caused by inappropriate waste handling of this product. For more detailed information about recycling of this product, please contact your local city office, your household waste disposal service or the shop where you purchased the product.

Remove transport safeguard


The appliance and the interior fittings are protected for transport.

• Remove all adhesive tape and packing pieces from the interior of the appliance.

Your appliance is equipped with shelf retainers that make it possible to secure the shelves during transportation.

To remove them proceed as follows:

Move the shelf retainers in the direction of the arrow, raise the shelf from the rear and push it forward until it is freed and remove the retainers.




Fitting the Door Handles

- 1. Screw the top handle bracket to the handle rod (1). Fit the bottom handle bracket on the lower lefthand side of the door (2).
- 2. Fit the top handle bracket on the top left-hand side of the door (3) and screw the handle rod to the bottom handle bracket (4).

Attention!

Do not overtighten the screws (max. 2 Nm) as you may damage the door handles.



Prior to Initial Start-Up

• Please clean the appliance interior and all accessories prior to initial startup (see section: "Cleaning and Care").

Starting up and temperature regulation

• Insert the plug of the connection lead into the plug socket with protective earth contact. When the refrigerator compartment door is opened, the internal lighting is switched on. The temperature selector knob is located on the RH side of the refrigerator compartment.

Setting "O" means: Off.

Setting "1" means: Hightest temperature, (warmest setting).

Setting "6" (end-stop) means: Lowest temperature, (coldest setting).

However, the exact setting should be chosen keeping in the mind that the temperature inside the refrigerator depends on:

-the quantity of food stored

-how often the door is opened

The temperatures in the refrigerator and freezer compartment cannot be independently regulated.

If you want the freeze fresh food rapidly, select setting "6", ensuring that the temperature in the refrigerator compartment does not drop blow 0°C. You should also promptly reset the temperature regulator to setting "3" or "4".

Important!


High ambient temperatures (e.g. on hot summer days) and a cold setting on the temperature regulator (position"5" to "6") can cause the compressor to run continuously.

If this happens, turn the temperature regulator back to a warmer setting (position "3" to "4"). At this setting the compressor will be switched on and off as usual and automatic defrosting recommenced.

Interior Accessories

Storage shelves

- You should always slide one of the full size glass storage shelf into the lowest set of guides, above the fruit and the vegetable containers, and keep it in this position.
- The height of the storage shelves can be adjusted:



- To do this pull the storage shelf forward until it can be swivelled upwards or downwards and removed.
- Please do the same in reverse to insert the shelf at a different height.

Adjusting the upper door rack

• Depending on the food stored, the upper door racks can be changed to other holders or removed. Take out the refrigerators food, press the door racks digonally upwards at their edges, reposition them, and press them back into place.

Fresh food refrigeration

To obtain the best performance:

- do not store warm food or evaporating liquide in the refrigeator
- do cover or wrap the food, particularly if it has a strong flavour.
- Position food so that air can circuiate freely round it.

Useful hints:

Meat (all types): wrap in polythene bags and place on the glass shelf above the vegetable drawer(s)For safety, store in this way only one or two days at the most.

Cooked foods, cold dishes, etc: these should be covered and may be placed on any shelf.

Fruit and vegetables: these should be thoroughly cleaned and placed in the special drawer(s) provided.

Butter and cheese: these should be placed in special airtight containers or wapped in aluminium foil or polythene bags to exclude as much air as possible.

Milk bootles: these should have a cap and should be stored in the bottle rack on the door.

Bananas, potatoes, onions and garlic, if not packed, must not be kept in the refrigerator.

Freezing and storing frozen food

You can use your freezer for freezing fresh food yourself.

Important!

- \bullet The temperature in the freezer compartment must be –18 °C or colder before freezing food.
- Please observe the freezing capacity given on the rating plate. The freezing capacity is the maximum quantity of fresh food that can be frozen within a period of 24 hours. If you wish to freeze food several days in a row, please observe a maximum capacity of only 2/3 to 3/4 of that on the rating plate. The quality of the food is best preserved when it is frozen right through to the core as quickly as possible.

- Allow warm food to cool down before freezing. The warmth will cause increased ice formation and increase the power consumption.
- Please note the maximum storage times specified by the manufacturer.
- Thawed foods which have not been processed further (cooked into meals) may not under any circumstances be frozen a second time.
- Containers with flammable gases or liquids can leak at low temperatures. There is a risk of an explosion! Do not store any containers with flammable materials such as, for example, spray cans, fire extinguisher refill cartridges etc in the refrigerator/freezer.
- Bottles and cans must not be placed in the freezer. They can burst when the contents freeze, high carbonate content drinks can even explode! Never store lemonade, juices, beer, wine, sparkling wine etc. in the freezer. Exception: high alcohol content spirits can be stored in the freezer.
- All foods must be packed air tight prior to freezing, so that they do not dry out or lose their flavour, and so that no flavour contamination of other frozen goods occurs.
- Not open the door frequently or leave it open longer than absolutely necessary.
- Unfrozen food must not touch items already frozen, otherwise the frozen food could begin to defrost.

Caution! Do not touch frozen food with wet hands. Your hands could freeze to the food.

1. Place the food to be frozen on the freezer shelf.

Preparation of Ice Cubes

- 1. Fill the ice cube tray 3/4 full with cold water, place it in the freezer compartment and leave to freeze.
- 2. To loosen the frozen cubes, either bend the ice cube tray or hold it under running water for a few seconds.

Important! Never try to free an ice tray that is frozen to the freezer compartment using pointed or sharp edged objects.

Freezing Calendar

• The symbols show different types of frozen goods.


• The numbers indicate storage times in months for the appropriate types of frozen goods. Whether the upper or lower value of the indicated storage time is valid depends on the quality of the foods and pre-treating before freezing. The lower value applies to foods with high fat content.

Defrosting

Refrigerator

Frost is automatically eliminated during normal use. The defrost water drains out through a trough into a special container at the back of the appliance, where it evaporates.

We recommend that you peridically clean the defrost-water drainage outlet with the cleaner provided, located in the center of the drainage groove.



Freezer

The freezer compartment, will become progressively covered with frost. This should be removed with a plastic scraper. Whenever the tickness of the frost exceeds 4 mm complete defrosting should be carried out as follows:

- 1. pull out the plug from the wall socket or turn the thermostat knob to th "0" setting.
- 2. remove any stored food, wrap it in several layers newspaper and put it in a coll place.
- 3. leave the door open.
- 4. when defrosting is completed, dry the interior thoroughly
- 5. turn the thermostat knob to the required setting or raplace the plug in the power socket.



Attention

Never use sharp metal tools to scrape off frost from the evaporator as you could damage it.

Do not use a mechanical device or any artificial means to speed up the thawing process other than those recommended by the manufacturer.

A temperature rise of the frozen food packs, during defrosting , may shorten their safe storage life.

Switching off the appliance

To switch off the appliance, turn the temperature regulator to position "0". If the appliance is not going to be used for an extended period:

- 1. Remove all refrigerated and deep-frozen packages as well as ice trays.
- 2. Switch off the appliance .
- 3. Remove the mains plug or switch off or turn out the circuit breaker or fuse.
- 4. Defrost freezer compartment and clean thoroughly (see section: "Cleaning and Care").
- 5. Leave the door open to avoid the build up of odours.

Cleaning and Care

Outside of the appliance

Important: Do not use cleaning agents for stainless steel or other aggressive or abrasive cleaning agents. The protective coat of lacquer on the stainless steel surface can be damaged by these.

The coat of lacquer protects against finger prints and therefore additional cleaning agents and maintenance products are no longer required.

- Clean the appliance with a cloth and lukewarm water. Commercially available dish washing detergents may also be used.
- After cleaning wipe with fresh water and rub dry.

For hygienic reasons the appliance interior, including interior accessories, should be cleaned regularly.

Warning!

- The appliance may not be connected to the mains during cleaning. Danger of electrical shock! Before cleaning switch the appliance offand rem ve the plug from the mains, or switch off or turn out the circuit breaker or fuse.
- Never clean the appliance with a steam cleaner. Moisture could accumulate in electrical components, danger of electrical shock! Hot vapours can lead to the damage of plastic parts.
- The appliance must be dry before it is placed back into service.

Attention!

- Ethereal oils and organic solvents can attack plastic parts, e.g.
- lemon juice or the juice from orange peals;
- butyric acid;
- cleansers which contain acetic acid.

Do not allow such substances to come into contact with appliance parts.

- Do not use any abrasive cleansers.
- 1. Remove frozen food and the food from the refrigerator. Wrap frozen food in several layers of newspaper. Store it in a cool place, well covered.
- 2. Defrost the freezer compartment prior to cleaning (see "Defrosting" section).
- 3. Switch the appliance off and remove the plug from the mains, or switch off or turn out the circuit breaker or fuse.
- 4. Clean the appliance and the interior accessories with a cloth and lukewarm water. Commercially available dish washing detergents may also be used.
- 5. After cleaning wipe with fresh water and rub dry.

Accumulation of dust at the condenser increases energy consumption. For this reason carefully clean the condenser at the back of the appliance once a year with a soft brush or a vacuum cleaner.

- 6. Check the water drain hole on the rear wall of the fridge. Clear a blocked drain hole with the aid of the green peg included with the appliance.
- 7. After everything is dry place appliance back into service.

Energy Saving Tips

- Do not install the appliance near cookers, radiators or other sources of warmth. High ambient temperatures cause longer, more frequent operation of the compressor.
- Ensure sufficient air circulation and exhaust at the appliance base and at the back wall of the appliance. Never cover air vent openings.
- Do not place warm foods into the appliance. Allow warm foods to cool first.
- Only leave door open as long as necessary.
- Do not set temperature any colder than necessary.
- Put frozen food in the fridge to defrost. The cold in the frozen food will then be used to cool the fridge.
- Always keep the heat emitting condenser, the metall grille on the rear wall of your appliance clean.

What to do if ... Correcting Malfunctions

A malfunction may be caused by only a minor fault that you can rectify yourself using the following instructions. Do not perform any other work on the appliance if the following information does not provide assistance in your specific case.

Warning! Repairs to refrigerators/freezers may only be performed by qualified service engineers. Improper repairs can give rise to significant hazards for the user. If your appliance needs repairing, please contact your specialist dealer or your local Service Force Centre.


Malfunction	Possible Cause	Remedy
Appliance does not work.	Appliance is not switched on	Switch on the appliance.
	Mains plug is not plugged in or is loose.	Insert mains plug.
	Fuse has blown or is defective.	Check fuse, replace if neces- sary.
	Socket is defective.	Mains malfunctions are to be corrected by an electrician.
Appliance cools too much.	Temperature is set too cold.	Turn the temperature regula- tor to a warmer setting tem- porarily.
The food is too warm.	Temperature is not properly adjusted.	Please look in the "Initial Star Up" section.
	Door was open for an exten- ded period.	Open the door only as long as necessary.
	A large quantity of warm food was placed in the appliance within the last 24 hours.	Turn the temperature regula- tor to a colder setting tempo- rarily.
	The appliance is near a heat source.	Please look in the "Installatior location" section.
Interior lighting does not work.	Light bulb is defective.	Please look in the "Changing the Light Bulb" section.
Heavy build up of frost, possibly also on the door seal.	Door seal is not air tight (pos- sibly after changing over the hinges).	Carefully warm the leaking sections of the door seal with a hair dryer (not hotter than approx. 50 °C). At the same time shape the warmed door seal by hand such that it sits correctly.
Unusual noises.	Appliance is not level.	Readjust the feet.
	The appliance is touching the wall or other objects.	Move the appliance slightly.
	A component, e.g. a pipe, on the rear of the appliance is touching another part of the appliance or the wall.	If necessary, carefully bend the component out of the way.
The compressor does not start immediately after changing the temperature setting.	This is normal, no error has occurred.	The compressor starts after a period of time.
Water on the floor or on sto- rage shelves.	Water drain hole is blocked.	See the "Cleaning and Care" section.

Changing the light bulb



Warning! There is a risk of electric shocks! Before changing the light bulb, switch off the appliance and unplug it, or pull the fuse or the circuit breaker. Light bulb data: Replace the lamp with one of the same power (the maximum power is shown on the light diffuser).

- 1. To switch off the appliance, turn the temperature regulator to position "0".
- 2. Unplug the mains plug.
- 3. To change the light bulb, undo the screw.
- 4. Press the light bulb cover as shown and slide it backwards.
- 5. Change the defective light bulb.
- 6. Refit the light bulb cover and the screw.
- 7. Put the refrigerator back into operation.



Service and Spare Parts

In the event of your appliance requiring service, or if you wish to purchase spare parts, please contact your local Service Force Centre by telephoning:

0870 5 929929

Your telephone call will be automatically routed to the Service Force Centre covering your post code area.

For address of your local Service Force Centre and further information about Service Force, please visit the website at <u>www.serviceforce.co.uk.</u>

Before calling out an engineer, please ensure you have read details under the heading "Something Not Working".

When you contact the Service Force Centre you will need to give following details:

1. Your name, address and post code

2. Your telephone number

3. Clear and concise details of the fault

4. The model and serial number of the apliance. (found on the rating plate).

5. The purchase date

Please note that a valid purchase receipt or guarantee documentation is required for in-guarantee service calls.

Customer Care Department

For general enquiries concerning your AEG-Electrolux appliance or for futher information on AEG-Electrolux products, please contact our Customer Care Department by letter or telephone at the address below or visit our website at www.aeg-electrolux.co.uk.

Customer Care Department AEG-Electrolux Major Appliances Addington Way Luton Bedfordshire LU4 9QQ Tel: 08705 350 350* *calls to this number may be recorded for training purposes

GUARANTEE CONDITIONS

Standard guarantee conditions

We, AEG-Electrolux, undertake that if within 12 months of the date of the purchase this AEG-Electrolux appliance or any part thereof is proved to be defective by reason only of faulty workmanship or materials, we will, at our discretion repair or replace the same FREE OF CHARGE for labour, materials or carriage on condition that:

• The appliance has been correctly installed and used only on the electricity or gas supply stated on the rating plate.

 \cdot The appliance has been used for normal domestic purposes only, and in accordance with the manufacturer's operating and maintenance instructions.

 \cdot The appliance has not been serviced, maintained, repaired, taken apart or tampered with by any person not authorised by us.

• All service work under this guarantee must be undertaken by a Service Force Centre. Any appliance or defective part replaced shall become the Company's property.

• This guarantee is in addition to your statutory and other legal rights.

 \cdot Home visits are made between 8.30am and 5.30pm Monday to Friday. Visits may be available outside these hours in which case a premium will be charged.

Exclusions

This guarantee does not cover:

· Damage or calls resulting from transportation, improper use or neglect, the replacement of any light bulbs or removable parts of glass or plastic.

 \cdot Costs incurred for calls to put right an appliance which is improperly installed or calls to appliances outside the United Kingdom.

 \cdot Appliances found to be in use within a commercial environment, plus those which are subject to rental agreements.

· Products of AEG-Electrolux manufacture which are not marketed by AEG-Electrolux.

European Guarantee

If you should move to another country within Europe then your guarantee moves with you to your new home subject to the following qualifications:

 \cdot The guarantee starts from the date you first purchased your product.

• The guarantee is for the same period and to the same extent for labour and parts as exists in the new country of use for this brand or range of products.

· This guarantee relates to you and cannot be transferred to another user.

· Your new home is within the European Community (EC) or European Free Trade Area.

 \cdot The product is installed and used in accordance with our instructions and is only used domestically, i.e. a normal household.

· The product is installed taking into account regulations in your new country.

Before you move please contact your nearest Customer Care centre, listed below, to give them details of your new home. They will then ensure that the local Service Organisation is aware of your move and able to look after you and your appliances.

France	Senlis	+33 (0)3 44 62 29 29
Germany	Nürnberg	+49 (0)800 234 7378
Italy	Pordenone	+39 (0)800 117511
Sweden	Stockholm	+46 (0)8 672 53 60
UK	Luton	+44 (0) 8705 350 350

Installation

Electrical Connection

Any electrical work required to install this appliance should be carried out by a qualified electrician or competent person.

WARNING - THIS APPLIANCE MUST BE EARTHED

The manufacturer declines any liability should these safety measures not be observed.

Before switching on, make sure the electricity supply voltage is the same as that indicated on the appliance rating plate. The rating plate is inside, on the left.

The appliance is supplied with a 13 amp plug fitted. In the event of having to change the fuse in the plug supplied, a 13 amp ASTA approved (BS 1362) fuse must be used.

Important!


The wires in the mains lead are coloured in accordance with the following code:

Green and Yellow Earth

Blue Neutral

Brown Live

As the colours of the wires in the mains lead of this appliance may not correspond with the coloured mark-ings identifying the terminals in your plug, proceed as follows:



- 1. The wire coloured green and yellow must be connected to the terminal marked with the letter "E" or by the earth symbol or coloured green and yellow.
- 2. The wire coloured blue must be connected to the terminal marked "N" or coloured black.
- 3. The wire coloured brown must be connected to the terminal marked "L" or coloured red.
- 4. Upon completion there must be no cut, or stray strands of wire present and the cord clamp must be secure over the outer sheath.

Warning! A cut-off plug inserted into a 13 amp socket is a serious safety (shock) hazard. Ensure that the cut-off plug is disposed of safely.

Positioning

This appliance should only be installed at a location where the ambient temperature corresponds to the climate classification indicated on the rating plate, which is located at the left on the inside of the appliance.

The following table shows which ambient temperature is correct for each climate classification:

For correct operation this appliance must be located in a dry atmosphere, away from heat sources, e.g. cookers, radiators, boilers and direct sunlight.


You should also ensure that air can circulate freely around the back and the top of the cabinet. There should be 100mm (4") between the top of the cabinet and any overhanging kitchenfurniture. Alternatively allow 50mm (2") between the top of the cabinet and any overhanging kitchen furniture and a gap of 25mm (1") on either side of the appliance.

Do not obstruct the space underneath. The back of the cabinet may be placed close to the wall but must not touch it. DO NOT install in places with restricted ventilation.

Adjust the level of the appliance by screwing out the adjustable foot, or feet, at the bottom of the cabinet using your fingers.

Rear spacers

Fit the rear spacers contained in the documentation bag to ensure escape of heat generated during operation. Proceed in the sequence illustrated in figures.



Reversing the door





The side at which the door hangs can be changed from the right side (factory supplied) to the left side, if the installation site requires.

Warning! When changing the side at which the door opens, the appliance may not be connected to the mains. Remove plug from the mains beforehand.

Proceed as follows:

- 1. Remove the clip-in ventilation grille (D).
- 2. Remove the bottom hinge (E) by unscrewing the fixing screws.
- 3. Slide the bottom door off the centre hinge (H).
- Remove the centre hinge and slide the top door off pin (G); unscrew pin (G) and refit it on the opposite side.
- 5. Remove the two plugs, to reveal the holes for the hinge pivots, and remount them on the other side.
- 6. Refit the top door and the centre hinge (H) on the opposite side.
- 7. Refit the bottom door.
- 8. Using a 10 mm spanner, unscrew the hinge pin (E) and reassemble it on the opposite side of the hinge;
- 9. Refit bottom hinge (E) on the opposite side, using the screws previously removed.
- 10. Remove blanking cover (F) from ventilation grille (D) by pushing it in the direction of the arrow and refit it on the opposite side.
- 11. Refit ventilation grille (D), clipping it into place.






- 12 Unscrew the top handle bracket from the handle rod (1). Unscrew the bottom handle bracket from the door (2).
- 13. Unscrew the top handle bracket from the door (3) and screw onto the bottom righthand side of the door (4).
- 14. Turn the handle bracket with the handle rod 180° and screw them to the door (5) and the fitted handle bracket (6).
- 15. Move the small plug from right to left.

Attention!

Do not overtighten the screws (max. 2 Nm) as you may damage the door handles.

After having reversed the opening direction of the doors check that all the screws are properly tightened and that the magnetic seal adheres to the cabinet. If the ambient temperature is cold (i.e. in Winter), the gasket may not fit perfectly to the cabinet. in that case, wait for the natural fitting of the gasket or accelerate this process by heating up the part involved with a normal hairdrier.



Regulations, Standards, Guidelines

This appliance was designed for household use and was manufactured in accordance with the appropriate standards. The necessary measures in accordance with appliance safety legislation regulations (GSG), accident prevention regulations for refrigeration appliances (VBG 20) and the regulations of the German Society of Electrical Engineers (VDE) were observed in the manufacture of this appliance.

The refrigerant circuit has been checked for leaks.

C $\mathbf{E}_{-73/23/EWG}^{\text{This appliance is in accordance with the following EU guidelines:}}$

- - 89/336/EWG dated 3 May 1989

(including guideline change notice 92/31/EWG) - EMV guideline

To buy accessories, consumables and spare parts at our online shop please visit: http://www.aeg-electrolux.co.uk

From the Electrolux Group. The world's No. 1 choice.

The Electrokus Group is the world's largest producer of powered appliances for kitchen, cleaning and outdoor use. More than 55 million Electrolux Group products (such as refrigerators, cookers, washing machines, vacuum cleaners, chain saws and lawn mowers) are sold each year to a value of apprix. USD 14 Million in more than 150 counties around the world.

AEG Hausgeräte GmbH Postfach 1036 D-90327 Nürnberg

http://www.aeg.hausgeraete.de

© Copyright by AEG 2223 324-81 02/06

Subject to change without notice